



Features:

- ◆ Waterproof IR Bullet Camera
- ◆ SONY/SHARP Color CCD
- ◆ IR LED: \varnothing 5X30pcs, IR Range:25M
- ◆ Lens: Board Lens 3.6mm/F2.0
- ◆ Water Resistance: IP66
- ◆ 3 - Axis Cable Built - in Bracket



◆ Specifications ◆

Model ID:	VW-HBC60	VW-HBH42	VW-HBS42	VW-HBS50	VW-HBH60	VW-HBS65	VW-HBS70
Description:	Waterproof IR Bullet Camera						
TV System:	NTSC/PAL						
Image Sensor:	1/3" Color CMOS CCD	1/4" Color SHARP CCD	1/3" Color SONY CCD	1/3" Color SONY CCD	1/3" Color SHARP CCD	1/3" Color SONY CCD	1/3" Color SONY
Horizontal resolution:	600 TV Lines	420 TV Lines	420 TV Lines	500 TV Lines	600 TV Lines	650 TV Lines	700 TV Lines
Effective Pixels:	PAL:500(H)x582(V)			PAL:752(H)x582(V)		PAL:752(H)x582(V)	PAL:976(H)x582(V)
	NTSC:510(H)x492(V)			NTSC:768(H)x494(V)		NTSC:768(H)x494(V)	NTSC:976(H)x494(V)
Sensitivity:	0.0005Lux/F2.0				0.001Lux/F2.0		
Lens:	3.6mm/6mm/8mm/12mm Board Lens /F2.0						
Sync, System:	Internal Synchronization						
Scanning System:	2:1 Interface						
Shutter Speed:	1/60~1/100,000sec (NTSC), 1/50~1/100,000sec (PAL)						
S/N Ratio:	≥48dB (AGC OFF)		≥52dB (AGC OFF)			≥115dB (AGC OFF)	
White Balance:	Auto						
AGC:	Auto				Auto/Manual		
BLC:	Auto						
OSD:	NO				YES		
WDR:	NO				YES		
NR:	NO				3D		2D
Power Source:	DC12V(9V ~ 15V), 500MA						
Operating Enviroment:	-20°C~60°C / 10% ~ 95%RH						
Working Humidity:	≤90%						
Size(mm):	162mm x72mm x 69mm						
Weight(kg):	0.85kg						